



BZTX-1A-300 | PILLOW PRODUCTION LINE

Functions & Applications

BZTX achieves full automation of pillow manufacturing, covering raw material handling, fiber opening, core filling, compression, packaging and delivery. Equipped with a PLC control system, the line only needs 2 operators, slashing labor costs. Standardized process control ensures consistent product quality and specifications.

Specifications	Bale opener machine	Fiber opening machine
Model	BSL-990	BSM-350
Work Voltage/Voltage	220V/60Hz	220V/60Hz
Motor Power/Power	3.3kw	8.25kw
Capacity/Processing Capacity	-	300-350kg/h
Dimensions (mm)	3900*1500*1950mm	2200*1300*1180mm

Specifications	Sucking machine	Mixing container	Fiber filling machine
Model	BSFJ-3.0	BHH-2.3	BCM-35
Work Voltage/Voltage	220V/60Hz	220V/60Hz	220V/60Hz
Motor Power/Power	3kw	2.2KW	3kw
Capacity/Processing Capacity	-	-	150 kg/h
Volume	-	2.3cbm	-
Air pressure	-	-	0.4-0.6mpa
Dimensions (mm)	700*550*580mm	1800*1060*1800mm	1100*580*970mm
Net Weight (kg)	80	270	90

